

# PROVA®



## AVM-301/ AVM-303 Anemometer

**Electrical Specifications: (23°C±5°C)**



### Range of Wind Velocity:

Units	Range	Resolution	Threshold	Accuracy
m/s	0.0 - 45.0	0.01	0.3	±3% ± 0.2
ft/min	0 - 8800	0.01/0.1/1	60	±3% ± 40
knots	0.0 - 88.0	0.01/0.1	0.6	±3% ± 0.4
Km/hr	0.0 - 160.0	0.01/0.1	1.0	±3% ± 0.8
mph	0.0 - 100.0	0.01/0.1	0.7	±3% ± 0.4

m/s: meter per second

ft/min: feet per minute

knots: nautical miles per hour

Km/hr: kilometers per hour

mph: miles per hour

### Unit Conversion table:

	m/s	ft/min	knots	Km/hr	mph
1 m/s	1	196.87	1.944	3.60	2.24
1 ft/min	0.00508	1	0.00987	0.01829	0.01138
1 knot	0.5144	101.27	1	1.8519	1.1523
1 Km/hr	0.2778	54.69	0.54	1	0.6222
1 mph	0.4464	87.89	0.8679	1.6071	1

## General Specifications:

Mounting Nut:	1/4" x 20
Operating Temperature:	Meter: 0 °C ~ 50°C (32 °F ~ 122°F) Vane: 0°C ~ 60°C (32 °F ~ 140°F)
Operating Humidity:	Less than 80% RH
Operating Pressure:	500 mB ~ 2 Bar
Storage Temperature:	-40°C ~ 60°C (-40°F ~ 140°F)
Power Consumption:	Approx. 6 mA
Battery Type:	1.5V AA batteries x 2
Battery Life:	200 hours (for 2000mA-hrs battery)
Dimension:	Meter: 78 x 130 x 40mm Vane: 66 x 132 x 29.2mm
Weight:	250g (battery included)
Accessories:	Carrying case x 1, Users manual x 1, 1.5V Battery x 2, <b>RS-232C to USB bridge (AVM-303)</b> <b>Software CD (AVM-303)</b> <b>Software Users Manual (AVM-303)</b>
Option:	<b>Prova 300XP Portable Thermal Printer (AVM-303)</b>


**PROVA<sup>®</sup>** **PROVA INSTRUMENTS INC.**

**Add:** 6F-2, #129, Lane 235, Pao-Chiao Road,  
Shin-Tien, Taipei Hsien 231, Taiwan

**Tel:** 886-2-89191255

**Fax:** 886-2-89191489

**E-mail:** [prova@ms3.hinet.net](mailto:prova@ms3.hinet.net)



صائين

**Tell:021-22900272-9**  
**WWW.SAENCO.COM**