

## ODP Series Programmable DC Power Supply

- + tow independent controllable channels
- + max output resolution : 1mV / 1mA
- + low ripples / low noise
- + up to 100 group timers



- + over-voltage / over-current protection
- + data-logging function: could record the output voltage, and current; and display recorded data in chart

- + 4 inch high resolution (480 x 320 pixels) LCD
- + multi- CI: USB, RS232, and LAN
- + auto-cooling system
- + SCPI, and LabVIEW supported

### ⊕ Performance Specifications

Model	ODP3122	ODP6062
Channel	2 (independent controllable channel)	
Max Output Power	378W	
Output Range	0 - 30V / 12A , 0 - 6V / 3A	0 - 60V / 6A, 0 - 6V / 3A

The specifications based upon the instrument having run for at least 30 minutes continuously, under the specified operating environment

Model	ODP3122	ODP6062	all 2 models
Channel	CH 1	CH 1	CH 2
Output Ratings (0°C - 40°C)	Voltage	0 - 30V	0 - 60V
	Current	12A	3A
Load Regulation	Voltage	$\leq 0.01\% + 3mV$	
	Current	$\leq 0.01\% + 3mA$	
Line Regulation	Voltage	$\leq 0.01\% + 3mV$	
	Current	$\leq 0.01\% + 3mA$	
Settings Resolution	Voltage	1mV	
	Current	1mA	
Read Back Resolution	Voltage	1mV	
	Current	1mA	
Settings Accuracy (25°C ± 5°C) (within 12 months)	Voltage	$\leq 0.03\% + 10mV$	
	Current	$\leq 0.1\% + 8mA$	
Read Back Accuracy (25°C ± 5°C)	Voltage	$\leq 0.03\% + 10mV$	
	Current	$\leq 0.1\% + 8mA$	
Noise and Ripple (20Hz - 20MHz)	Voltage (Vp-p)	$\leq 4mVp-p$	
	Voltage (rms)	$\leq 1mVr$	



	Current (rms)	$\leq 5\text{mArms}$	$\leq 4\text{mA rms}$
Temperature Coefficient (0°C - 40°C)	Voltage	$\leq 0.03\% + 10\text{mV}$	
	Current	$\leq 0.1\% + 5\text{mA}$	
Read Back Temperature Coefficient	Voltage	$\leq 0.03\% + 10\text{mV}$	
	Current	$\leq 0.1\% + 5\text{mA}$	
Parallel Settings Accuracy	Voltage	$\leq 0.02\% + 5\text{mV}$	
	Current	$\leq 0.1\% + 30\text{mA}$	
Programmable Output	Storage	100 groups	
	Time Setting	second	
Data Recording	10 K groups (of voltage, current and power data) recording capacity		
Working Temperature	0 - 40°C		
Communication Interface	USB, RS232, and LAN		

Specifications subject to change without prior notice.

Display	ODP3122	ODP6062
LCD Type		4 inch color LCD
Display Resolution		480 x 320 pixels, 65536 colors

Mechanical Specifications	ODP3122	ODP6062
Dimension (W x H x D)	250 x 158 x 358 (mm)	
Device Weight	12.00 kg	

## + Application

R&D laboratory                            QC test  
automobile, and electronic circuit test

## industrial automation test education / teaching experimentation


**+** **Accessories** The accessories subject to final delivery.



## Power Cord



CD




Manual



## USB Cable



Fuse



### Test Leads ( optional)

شرکت صائن

[WWW.SAENCO.COM](http://WWW.SAENCO.COM)

021 88936611

