

Portable Free & Total Chlorine Meter



FTC-420

Features

- Microprocessor based for fast and accurate measurements.
- EPA approved DPD method.
- Large LCD 45 x 25 mm display for reading convenient.
- Memory function stores and recalls up to 150 points.
- Low battery alarm and auto shut off after 10 minutes of non use.

Specifications

| | Free & Total Chlorine |
|-------------|---|
| Range | 0 ~ 5.00 ppm |
| Resolution | 0.01 ppm |
| Accuracy | ± 0.03 + 1 digit at <2.00 ppm ± 3% FS + 1 digit at >2.00 ppm |
| Response | <5 seconds |
| Operating | 0 ~ 50 °C, <85% RH |
| Sample | 10 ml |
| Data memory | Storage /recall up to 150 points |
| Power | DC 1.5V (UM4, AAA) battery x 4 pcs |
| Dimension | Meter: 70 x 135 x 65 mm |
| Weight | Meter: 168 g (including battery) |

Standard Accessories

Reagent strip x 50 pcs, Testing bottle x 3, Battery, Clean cloth, Cup, Distilled water, Manual, Carrying case



Portable Turbidity Meter



TUB-430

Features

- Microprocessor based for fast and accurate measurements.
- Measurement method meet ISO 7027.
- Large LCD 45 x 25 mm display for reading convenient.
- Unit NTU, FTU, EBC are changeable.
- Memory function stores and recalls up to 150 points.
- Low battery alarm and auto shut off after 10 minutes of non use.

Specifications

| | Turbidity |
|-------------|--|
| Range | 0 ~ 19.99 NTU |
| | 20.0 ~ 199.9 NTU |
| | 200 ~ 1000 NTU |
| Resolution | 0.01/0.1/1 NTU |
| Accuracy | ± 3% of reading + 1 digit at <500 NTU ± 5% of reading + 1 digit at >500 NTU |
| Response | <10 seconds |
| Operating | 0 ~ 50 °C, <85% RH |
| Sample | 10 ml |
| Data memory | Storage /recall up to 150 points |
| Power | DC 1.5V (UM4, AAA) battery x 4 pcs |
| Dimension | Meter: 70 x 135 x 65 mm |
| Weight | Meter: 168 g (including battery) |

Standard Accessories


Standard solution set, Testing bottle x 2, Battery, Clean cloth, Cup, Distilled water, Manual, Carrying case



شركت صائن

WWW.SAENCO.COM

021 88936611



www.gondo.com.tw

