



WATER QUALITY TESTER 6 IN ONE COMBO PEN

NEW



Features

- A very smart pen type combo water quality tester
- Buy one get more than 6 parameter measurement
- A new shape design powered by AAA batteries
- Microprocessor based for fast and accurate measurements.
- Simple to calibrate by one button
- Compact housing Ip57 water resistant design
- It may float on water
- Large LCD display pH or ORP or Cond. or TDS or Salt and temperature simultaneously
- ATC stands for Automatic Temperature Compensation
- MSC stands for Manually salinity calibration
- MAC stands for Manually altitude compensation
- Multi-function with Data hold freezes current reading
- Maximum/Minimum function
- Temperature units C or F selectable
- Low battery and consumption indicator
- Auto power off of no use in 10 minutes
- Easy to replace with new electrode to maintain meter life
- Replacement electrode modules are easy to replace and the type of electrode would be recognized automatically and shown in display during insertion
- Complete package includes meter , wrist strip, pH, Cond. electrodes and pH(4.7), Cond(1413uS) solution ,soaking solution ,operation manual in a hard carrying case.
- Optional: ORP electrode (98P70). pH 10.01 and Cond. 12.88mS solution



(Complete package)



ORP Level (mV)	Application
0-150	No practical use
150-250	Aquaculture
250-350	Cooling Towers
400-475	Swimming pools
450-600	Hot Tubs
600	Water Disinfection *
800	Water Sterilization **

Specifications

Model No.	99720					
Type	pH	mV	Temp.	Cond.	TDS	Salt
Range	-2~16.00	-1000~1000	0~90°C	0~2000µS, 2.00~20.00mS	0~1300ppm 1.30~13.00ppt	0~1000ppm, 1.00~12.00ppt
Accuracy	±0.01 + 1 digit	±2 + 1 digit	±0.2°C + 1 digit	±2%FS (Cond. TDS Salt)		
Resolution	0.01pH	1mV	0.1°C	1µS/ 0.01mS	1ppm/ 0.01ppt	1ppm/ 0.01ppt
ATC	0~90°C	N/A	N/A	0~50°C		
Calibration	pH: 4.00/ 7.00/ 10.01			Cond: 0µS/ 1413µS/ 12.88mS		
Power	AAA (UM-4) size batteries x 4 pcs					
Weight	Meter : 135 g (battery included)					
Dimension	Meter : 170 X 33.5mm					

