

# **TES**

## 1260 Humidity Temperature Meter

### FEATURE:

- Dual LCD display.
- Dew Point Reading.
- Wet bulb Reading.
- MAX/MIN with Time Stamp.
- Data Hold function.
- °C / °F Switchable.
- DATA memory and read function.  
(99 readings from LCD display)
- Auto Power Off.



### SPECIFICATIONS

<b>Measuring Range</b>	Temperature : -20°C ~ 60°C (-4°F ~ 140°F) Humidity : 1%RH ~ 99%RH
<b>Resolution</b>	0.1°C / 0.1°F / 0.1%RH
<b>Accuracy</b>	Temperature : ±0.5°C, ±0.9°F Humidity : ±3%RH ( at 25°C, 30 ~ 99% RH ). ±5%RH ( at 25°C, 1 ~ 30% RH ).
<b>Data Memory capacity</b>	Manual recording : 99 data sets. (Direct reading from LCD display.)
<b>Sampling Rate</b>	2 times/sec
<b>Operating Conditions</b>	0°C ~ 60°C (32°F ~ 140°F) & below 99% R.H. (no condensation)
<b>Power Source</b>	9V Battery
<b>Battery Life</b>	Approx. 200 hours.
<b>Size &amp; Weight</b>	193mm(L) × 59mm(W) × 26mm(H) / 140g
<b>Accessories</b>	Instruction manual, Battery, Carrying case.

# **TES**

### TES ELECTRICAL ELECTRONIC CORP.

7F, No. 31, Lane 513, Rui Guang Road, Neihu Dist. Taipei, Taiwan, R. O. C.  
Tel : (02) 2799-3660  
E-Mail Address : tes@ms9.hinet.net

Fax : 886-2-2799-5099  
<http://www.tes.com.tw>