


TES

Reliable in Quality

شرکت صائن

WWW.SAENCO.COM

021 88936611




TES-1386/1387 TURBIDITY METER

- ❑ Auto-ranging from 0 to 1000 NTU
- ❑ Waterproof and dustproof with IP67-rated housing that floats!
- ❑ Meets performance criteria as specified by ISO 7027 (DIN EN 27027) method
- ❑ Compliant with ASTM D6855-03 (EPA recognized)
- ❑ Four point push-button calibration for full-range accuracy
- ❑ Manual data memory and read function
- ❑ Auto data logger function (1387)
- ❑ USB Interface (1387)

Application :

Test Tap water, food and beverage water ... etc.





1386/1387 TURBIDITY METER

FEATURES

- Auto-ranging from 0 to 1000 NTU
- Waterproof and dustproof with IP67-rated housing that floats!
- Meets performance criteria as specified by ISO 7027 (DIN EN 27027) method
- Compliant with ASTM D6855-03 (EPA recognized)
- Four point push-button calibration for full-range accuracy
- Manual data memory and read function
- Auto data logger function (1387)
- USB Interface (1387)

SPECIFICATIONS

| | |
|-----------------------------|---|
| Min Turbidity | 0.01 |
| Max Turbidity | 1000 |
| Turbidity Resolution | 0.01, 0.1, or 1 NTU |
| Turbidity Accuracy | ±2% of reading |
| Data memory capacity | 99 sets. (Direct reading from LCD display) |
| Data logger capacity | microSD CARD 4 GB (1387) |
| Min Temperature | 0°C/32°F |
| Max Temperature | 50°C/122°F |
| Waterproof | IP67 |
| Battery | 4 x AAA batteries |
| Size | 148mm x 78mm x 64mm |
| Accessories | carrying case, 10-mL silicone oil, Lint-free cloth, four standard solutions, four standard cuvettes, three sample cuvettes, 4 AAA batteries CD Software (1387), micro-USB Cable (1387) |